

Technical datasheet

Topshield

Drying accelerator for Liquid Rubber

Topshield is a highly concentrated, environmentally friendly accelerator for various products from Liquid Rubber. **Topshield** is applied on top of the Liquid Rubber product, which accelerates the curing time of the Liquid Rubber product. **Topshield** immediately removes a large part of the moisture percentage of Liquid Rubber causing an immediate "skin formation" on the Liquid Rubber product. This causes the products to dry faster and more resistant to, for example rainfall.

Topshield is an environmentally friendly product and can be used indoors and outdoors without special protection.

APPLICATION

Topshield is available in 1L bottles with spray trigger. Spray **Topshield** lightly over the Liquid Rubber product with an average distance of +- 20cm from the surface. The top layer of the product will be dry to touch immediately.

RESTRICTIONS

Obey the safety precautions when applying by wearing gloves, eye protection and other suitable protective equipment. Please refer to the SDS sheet for more information.

PHYSICAL PROPERTIES (liquid)

Properties

Color
Specific gravity (liquid), g/cm³
Odor

Typical results

Transparant
CA. 1.0
None



WARNING

Topshield should not be applied when the ambient temperature is lower than 0°C. During extreme rainfall is not recommended to use **Topshield**. For professional use only. Keep out of reach of children. Do not store product in direct sunlight, maximum 32°C (90°F) and minimum 5°C (41°F).

TECHNICAL SERVICE

T: +31 (0)297 587866
F: +31 (0)297 587861
E: info@liquidrubbereurope.com
W: www.liquidrubbereurope.com

Groot Mijdrechtstraat 15
3641 RV Mijdrecht

V1 – 08/2020