Yuasa Datablad

Yuasa RE12-12 Industrial VRLA Battery

Specifikationer

Nominell spänning (V)	12
10h flöde kapacitet till 1.8V/Cell vid 20°C (Ah)	10.56
20h flöde kapacitet till 1.75V/Cell vid 20°C (Ah)	12

Dimensioner

Längd (mm)	151 (±1)
Bredd (mm)	98 (±1)
Höjd (mm)	94 (±1)
Höjd över terminalerna (mm)	98 (±2)
Vikt (kg)	4.15 (4.4)

Poltyp

FASTON - Quickfit / release (JST where stated)	6.35

Drifttemperatur område

Lagring (i fulladdat tillstånd)	-15°C to +45°C
Ladda	-15°C to +45°C
Urladdning	-15°C to +45°C

Lagring

Självurladdning per månad vid 20°C (cirka %)	3

Yttermaterial

Standard	ABS (UL94:HB)
Flamsäker (FR) tillgänglig	UL94:V0

Laddningsspänning

Underhållsladdning vid 20°C (V)/Block	13.65 (±1%)
Underhållsladdning vid 20°C (V)/cell	2.275 (±1%)
Hålladdningsspänning temp korrektionsfaktor vid 20°C (mV)	-3
Cyklisk (boost) laddningsspänning vid 20°C (V)/Block	14.5 (±3%)
Cyklisk (boost) laddningsspänning vid 20°C (V)/cell	2.42 (±3%)
Cyklisk drift, laddningsspänning temperatur korrektionsfaktor vid 20°C (mV)	-4

Laddningsström

Underhållsladdning strömbegränsning (A)	No limit
Cylisk (boost) laddning strömbegränsning (A)	3

Max. urladdningsström

1 sekund (A)	180
1 minut (A)	24


Impedans

mätt vid 1 kHz (mΩ)	15

Livslängdsklass & godkännanden

EUROBAT Klassificering: General Purpose	6 to 9 years
Yuasa livslängdsklass vid 20°C (år)	up to 10 years

Layout



3:e parts certifiering

ISO9001 - Kvalitetsledningssytem
UNDERWRITERS LABORATORIES Inc.

Cert. No.: FM 10626

Säkerhet

Installation

Kan installeras och användas i riktningar upp till 90° från upprätt läge.

Handtag

Batterierna får inte monteras hängande i handtagen.

Backventil

Varje cell är försedd med en ventil för att tillåta gaser att undkomma och sedan återförsluta .

Gasutsläpp

VRLA-batterier kan bilda vätgas som kan skapa explosiva blandningar i luften. Placera inte batteriet inuti en sluten behållare

Återvinning

YUASA VRLA-batterier måste återvinnas i enlighet med lokala och nationella lagar och förordningar.


Kalkylark genererad 19/11/2024 – E&OE

Yuasa Technical Data Sheet

Yuasa RE12-12 Industrial VRLA Battery

Specifications	
Nominal voltage (V)	12
10-hr rate Capacity to 1.8V/Cell at 20°C (Ah)	10.56
20-hr rate Capacity to 1.75V/Cell at 20°C (Ah)	12
Dimensions	
Length (mm)	151 (±1)
Width (mm)	98 (±1)
Height (mm)	94 (±1)
Height over terminals (mm)	98 (±2)
Mass (kg)	4.15 (4.4)
Terminal Type	
FASTON - Quickfit / release (JST where stated)	6.35
Operating Temperature Range	
Storage (in fully charged condition)	-15°C to +45°C
Charge	-15°C to +45°C
Discharge	-15°C to +45°C
Storage	
Capacity loss per month at 20°C (% approx.)	3
Case Material	
Standard	ABS (UL94:HB)
FR version available	UL94:V0
Charge Voltage	
Float charge voltage at 20°C (V)/Block	13.65 (±1%)
Float charge voltage at 20°C (V)/Cell	2.275 (±1%)
Float Chg voltage tmp correction factor from std 20°C (mV)	-3
Cyclic (or Boost) charge Voltage at 20°C (V)/Block	14.5 (±3%)
Cyclic (or Boost) charge Voltage at 20°C (V)/Cell	2.42 (±3%)
Cyclic Chg voltage tmp correction factor from std 20°C (mV)	-4
Charge Current	
Float charge current limit (A)	No limit
Cyclic (or Boost) charge current limit (A)	3
Maximum Discharge Current	
1 second (A)	180
1 minute (A)	24
Impedance	
Measured at 1 kHz (mΩ)	15
Design Life & Approvals	
EUROBAT Classification: General Purpose	6 to 9 years
Yuasa design life at 20°C (yrs)	up to 10 years

Layout



3rd Party Certifications
ISO9001 - Quality Management Systems
UNDERWRITERS LABORATORIES Inc.

Safety

Installation
Can be installed and operated in orientations up to 90° from the upright position.

Handles
Batteries must not be suspended by their handles (where fitted).

Vent valves
Each cell is fitted with a low pressure release valve to allow gasses to escape and then reseal.

Gas release
VRLA batteries release hydrogen gas which can form explosive mixtures in the air. Do not place inside a sealed container.

Recycling
YUASA's VRLA batteries must be recycled at the end of life in accordance with local and national laws and regulations.

Data Sheet generated on 19/11/2024 – E&OE