



TECHNICAL SPESIFICATION

Power Splitter Low PIM

Art.nr 586842

Art.nr 586843

Art.nr 586857



2-WAY SPLITTER LOW PIM ART.NR 586842

3-WAY SPLITTER LOW PIM ART.NR 586843

4-WAY SPLITTER LOW PIM ART.NR 586857

Art.nr	586842	586843	586857
Frequency Range	698-4200 MHz		
Band Support	1/3/7/8/20/28L/28U/40/n48/n78/n77		
Input Port Number	1		
Output Port Number	2	3	4
Connectors	4.3-10-Female		
Power Divider Class	Wilkinson		
Insertion Loss (dB)	≤1.0	≤1.5	≤1.5
Splitt Loss (dB)	3.0	4.8	6.0
Port Isolation (dB)	≥22	≥20	≥18
VSWR	≤1.3		
3 rd PIM	≤-153dBc@2*43dBm		
Input Impedance	50Ω		
Average Power	50W (46.99dBm)		
Color	Black		
Operating Temp.	-30 °C to +70 °C		
IP Rating	IP65		
Dimensions	120 x 60 x 29mm	225 x 45 x 29mm	142.5 x 121 x 29mm
RoHS	Compliant		

MECHANICAL DRAWING

