

## Note

The adaptations recommended by us in this list have been determined with sample valves available to us and relate to the specifications indicated by the manufacturer. For this, we consider the tolerance indications of the valve manufacturers as far as known, or we assume common tolerances/safety factors in order to ensure a correct function.

The mentioned adaptations ensure a solely mechanical compatibility to our adapter system and our actuators. The user must select an appropriate actuator from our portfolio, taking into account our corresponding data sheets and technical documentation of the valve/ the distributor. A liability of Möhlenhoff for this selection is excluded.

We always keep our adapter lists current and publish necessary adaptations in due time, stating the version date.

However we do not have any direct influence on manufacturing tolerances or design changes of the valve manufacturers.

Therefore, the indicated recommendations are subject to design changes of the respective manufacturers. We hereby exclude any liability for malfunctions due to constructive changes or deviations not known to us as well as due to dimensional variations caused by the valve manufacturers.

You can find the current adapter list in the download area of the OEM partner portal in the actuator section.



We are always at your disposition for questions.

Technical Service Möhlenhoff





Tel.: +49 (0) 5341 8475 470

Fax: +49 (0) 5341 8475 477

e-mail: [service@moehlenhoff.de](mailto:service@moehlenhoff.de)







## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
Adaptation on request	Oventrop HyCocon 1M, Oventrop Q1Z Tour Andersson TA-Compact-P Meibes Ballorex Honeywell V5822A4000, V5832A4008 Schneider Electric PIBCV Frese Optima Compact 5mm and 5.5mm Siemens VPP46 und VPI46 5mm and 5.5mm					
VA02	Velta Euro manifold Uponor (Afriso) proVario Uponor Vario Plus		 <p><b>VA 02</b> Part-No.: 108633 Thread : M30x1,5 (outside) Pin color : <i>Crimson (UN 3048)</i> Pin length : 28 Adaptor color : <i>grey (UN 7053)</i></p>			17,00
VA 04	Beulco (before 2005)		 <p><b>VA 04 H</b> Part-No.: 108642 Thread : M30x1,0 Pin color : <i>light blue (UN 5025)</i> Pin length : 14 Adaptor color : <i>grey (UN 7053)</i></p>	 <p><b>VA 04 HK</b> Part-No.: 110945 Thread : M30x1,0 Pin color : <i>light blue (UN 5025)</i> Pin length : 19 Adaptor color : <i>sapphire blue (UN 7047)</i></p>	 <p><b>VA 04 H-SK</b> Part-No.: on request Thread : M30x1,0 Pin color : <i>light blue (UN 5025)</i> Pin length : 14 Adaptor color : <i>grey (UN 7053)</i></p>	6,00










## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
<b>VA 08</b>	Reich Valves		 <p><b>VA 08 H</b> Part-No.: 108764 Thread : M30x1,0 Pin color : <i>chocolate brown (UN 8051)</i> Pin length : 13,5 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 08 H-SK</b> Part-No.: 126461 Thread : M30x1,0 Pin color : <i>chocolate brown (UN 8051)</i> Pin length : 13,5 Adaptor color : <i>grey (UN 7053)</i></p>	6,50
<b>VA 10</b>	<p>Dumser, Beulco (as of 2005), Purmo, Strawa Oventrop (also Cocon, Cocon 4, Tri-D, Tri-M) Oventrop Thermostatic valves Vescal (Metaplast), Wittingsthal, Frasa, Cronatherm (H), eht Siegmund KaMo (H) before Sept. 2005, Aquatherm (brass), Valvex brass manifold, Thermtec Viega stainless steel manifold (Fonterra &amp; pro Radiant), Sauter (VUT015 F210) (VUL010 F330 &amp; F340) Thermotech Schweden, KaMo INOX-manifold Bianchi valves (Serie 401T &amp; 403T) Bianchi brass manifold (Serie 332T) Unipipe (ECO-manifold), CronaTech, KAN-Therm (stainless steel manifold), Fränkische Siemens (Landis &amp; Steafa) VPD 115A, Nereus (valve DN20), Zehnder, ATS stainless steel-manifold Tour &amp; Andersson (TBV-CM, TBV-CMP, TBV-CNF) Frese Optima Compact (2,5mm &amp; 4mm), Formare (No.80) Hesag / Herb (manifold Profi-Line), Luxor (CD-manifold) Gampper (Th.-valves Standard, Vario Q) Gampper (manifold), Comisa (FXF-3) stainless steel Oventrop stainless steel manifold TECE stainless steel (Strawa) Watts brass manifold (HKV-T), Tiemme valves, Watts (Vogel &amp; Noot, Cosmo Objektline), Artiga, Acome (Strawa), Multibeton HKV (Strawa) Emcal (Modell 1998), U-Tube stainless steel manifold GTGlobe Industries, Henco VUFLD-02 brass Afiso Pro Calida MC1, redh (HKV3) Tobler Stramax (220TTT-07-04S), (220TA2-06-04D) Gerken &amp; Schulte, Pipe Fittings Company Italia</p>	 <p><b>VA 10</b> Part-No.: 108478 Thread : M30x1,5 Adaptor color : <i>light grey (UN 7019)</i></p>	 <p><b>VA 10 H</b> Part-No.: 108641 Thread : M30x1,5 Pin color : <i>light grey (UN 7019)</i> Pin length : 9 Adaptor color : <i>grey (UN 7053)</i></p>	 <p><b>VA 10 HK</b> Part-No.: 110937 Thread : M30x1,5 Pin color : <i>light grey (UN 7019)</i> Pin length : 14 Adaptor color : <i>light blue (UN 55088)</i></p>	 <p><b>VA 10 H-SK</b> Part-No.: 114256 Thread : M30x1,5 Pin color : <i>light grey (UN 7019)</i> Pin length : 9 Adaptor color : <i>grey (UN 7053)</i></p>	11,00








## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 13	Albert, ThermoLutz, Aquatherm (Variomat to ca. 1993)		 <p><b>VA 13 H</b> Part-No.: 116550 Thread : M30x1,5 Pin color : <i>black</i> Pin length : 8,5 Adaptor color : <i>white (RAL 9010)</i> Adaptor is extra high (+3mm)</p>		 <p><b>VA 13 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin color : <i>black</i> Pin length : 8,5 Adaptor color : <i>white (RAL 9010)</i> Adaptor ist extra high (+3mm)</p>	14,50
VA 15	Herz (Kombivalve-Volume-flow-controller, 1 4006 21)		 <p><b>VA 15 H</b> Part-No.: 129286 Thread : M28x1,5 Pin Color : <i>orange (UN 2002)</i> Pin length : 11,5 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 15 H-SK</b> Part-No.: on request Thread : M28x1,5 Pin Color : <i>orange (UN 2002)</i> Pin length : 11,5 Adaptor color : <i>grey (UN 7053)</i></p>	8,50
VA 16	Herz Thermostaticvalves Serie 'TS 98 V' FB - manifold 3-way-valve type 'Calis TS RD' control valve type 'TS 99 FV' (H) control valve type 'TS V'  Polytherm (H), Thermoval, Buderus KAN-Therm (brass manifold)	 <p><b>VA 16</b> Part-No.: 108468 Thread : M28x1,5  Adaptor color : <i>red (UN 3004)</i></p>	 <p><b>VA 16 H</b> Part-No.: 108636 Thread : M28x1,5 Pin Color : <i>red (UN 3004)</i> Pin length : 11,75 Adaptor color : <i>grey (UN 7053)</i></p>	 <p><b>VA 16 HK</b> Part-No.: 110948 Thread : M28x1,5 Pin Color : <i>red (UN 3004)</i> Pin length : 16,75 Adaptor color : <i>dark blue (UN 5023)</i></p>	 <p><b>VA 16 H-SK</b> Part-No.: 133416 Thread : M28x1,5 Pin Color : <i>red (UN 3004)</i> Pin length : 11,75 Adaptor color : <i>grey (UN 7053)</i></p>	8,25
VA 17	MMA (EDVH 25, FVXR 15, VXR 20) ICMA (BAS) Industrietechnik Italy (DB VZ2)	 <p><b>VA 17</b> Part-No.: 110611 Thread : M28x1,5  Adaptor color : <i>pure white (RAL 9010)</i></p>				11,50












## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 18	Honeywell & Braukmann with high thread approach (else VA 50) (only valves with 2,5mm stroke, z.B. V5833C 4003) Landis & Gyr VD115-80 Tour Andersson (VZ32)	 <p><b>VA 18</b> Part-No.: 112486 Thread : M30x1,5</p> <p>Adaptor color : <i>light blue (UN 5029)</i></p>				10,50
VA 19	Deca Viega brass manifold (till May 2007)		 <p><b>VA 19 H</b> Part-No.: 108775 Thread : M30x1,5 Pin Color : <i>chocolate brown (UN 8051)</i> Pin length : 13,5 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 19 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : <i>chocolate brown (UN 8051)</i> Pin length : 13,5 Adaptor color : <i>grey (UN 7053)</i></p>	6,50
VA 20	Schlösser (before 1993) Viega brass manifold (from May 2007)		 <p><b>VA 20 H</b> Part-No.: 109935 Thread : M30x1,5 Pin Color : <i>yellow (UN 1069)</i> Pin length : 13 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 20 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : <i>yellow (UN 1069)</i> Pin length : 13 Adaptor color : <i>grey (UN 7053)</i></p>	7,00
VA 21	Conec		 <p><b>VA 21 H</b> Part-No.: 108763 Thread : M30x1,5 Pin Color : <i>Sapphire blue (UN 5047)</i> Pin length : 14,5 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 21 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : <i>Sapphire blue (UN 5047)</i> Pin length : 14,5 Adaptor color : <i>grey (UN 7053)</i></p>	5,50










## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 26	Giacomini Giacomini corner valve (H)	 <b>VA 26</b> Part-No.: 108474  Adaptor color : grey (UN 7053)	 <b>VA 26 H</b> Part-No.: 109322 Thread : M30x1,5 Pin Color : light blue (UN 5025) Pin length : 14 Adaptor color : grey (UN 7053) With additional adaptor for Giacomini		 <b>VA 26 H-SK</b> Part-No.: 129503 Thread : M30x1,5 Pin Color : light blue (UN 5025) Pin length : 14 Adaptor color : grey (UN 7053) With additional adaptor for Giacomini	4,20
VA 28	Honeywell & Braukmann with high thread approach (else VA 50) (valves with 6,5mm stroke, as V5832A 4003)	 <b>VA 28</b> Part-No.: 119861 Thread : M30x1,5  Adaptor color : red (UN 3004)				11,50
VA 30	FAR (till 2007) Danfoss-valves VZL2 & VZL4 Frese EVA High		 <b>VA 30 H</b> Part-No.: 108901 Thread : M30x1,5 Pin Color : dark blue (UN 5023) Pin length : 11 Adaptor color : white grey (UN 7002)	 <b>VA 30 HK</b> Part-No.: 110942 Thread : M30x1,5 Pin Color : dark blue (UN 5023) Pin length : 16 Adaptor color : light blue (UN 55088)	 <b>VA 30 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : dark blue (UN 5023) Pin length : 11 Adaptor color : white grey (UN 7002)	9,00
VA 31	Tour & Andersson (older valve type 'RVT 40')		 <b>VA 31 H</b> Part-No.: 129267 Thread : M28x1,5 Pin Color : dark green (UN6090) Pin length : 10,5 Adaptor color : grey (UN 7053)		 <b>VA 31 H-SK</b> Part-No.: on request Thread : M28x1,5 Pin Color : dark green (UN6090) Pin length : 10,5 Adaptor color : grey (UN 7053)	9,50
VA 32	Tour & Andersson brass manifold Nereus type9440 (corner valve) Uponor brass manifold (Vario B WGF)	 <b>VA 32</b> Part-No.: 108467 Thread : M28x1,5  Adaptor color : light green (UN 6026)		 <b>VA 32 HK</b> Part-No.: 110949 Thread : M28x1,5 Pin Color : light green (UN 6026) Pin length : 17,25 Adaptor color : dark blue (UN 5023)		7,75









## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 33	Wirsbo Canada redh (Multi-Therm manifold) Tour & Andersson valve RVT 40 Johnson Controls (VG5810AC)	  <b>VA 33</b> Part-No.: 109429 Thread : M28x1,5  Adaptor color : <i>light grey (UN 7019)</i>		  <b>VA 33 HK</b> Part-No.: 110946 Thread : M28x1,5 Pin Color : <i>dark grey (UN 7028)</i> Pin length : 15 Adaptor color : <i>dark blue (UN 5023)</i>		10,00
VA 34	Pintossi		  <b>VA 34 H</b> Part-No.: 109316 Thread : M26x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>grey (UN 7053)</i>	  <b>VA 34 HK</b> Part-No.: 111610 Thread : M26x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 14,5 Adaptor color : <i>light blue (UN 55088)</i>	  <b>VA 34 H-SK</b> Part-No.: on request Thread : M26x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>grey (UN 7053)</i>	10,50
VA 39	Oventrop (before 1997) Viega Kanada (3-way valve, older 2000)	  <b>VA 39</b> Part-No.: 108471 Thread : M30x1,0  Adaptor color : <i>pure white (RAL 9010)</i>	  <b>VA 39 H</b> Part-No.: 108638 Thread : M30x1,0 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>grey (UN 7053)</i>	  <b>VA 39 HK</b> Part-No.: 110944 Thread : M30x1,0 Pin Color : <i>white grey (UN 7002)</i> Pin length : 14,5 Adaptor color : <i>Sapphire blue (UN 5047)</i>	  <b>VA 39 H-SK</b> Part-No.: 113127 Thread : M30x1,0 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>grey (UN 7053)</i>	10,50

## Übersicht - Ventiladapter











Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
<b>VA 41</b>	Aquatechnik Italy (Multirapid, 2007 bis 2009) Vescal (Cazzaniga) Danfoss AB-QM (DN10 - DN20) (4mm actuator) Danfoss AB-QM (DN25 - DN32) (5mm actuator) RDZ (plastic-manifold) Frese EVA Basic (from 2016) + 5mm actuator	 <b>VA 41</b> Part-No.: 110501 Thread : M30x1,5  Adaptor color : <i>dark green (UN6090)</i>	 <b>VA 41 H</b> Part-No.: 112447 Thread : M30x1,5 Pin Color : <i>dark green</i> Pin length : 10,5  Adaptor color : <i>white grey (UN 7002)</i>		 <b>VA 41 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : <i>dark green</i> Pin length : 10,5  Adaptor color : <i>white grey (UN 7002)</i>	9,50
<b>VA 44</b>	Cazzaniga (old)		 <b>VA 44 H</b> Part-No.: 109627 Thread : M32x1,5 (outside) Pin Color : <i>cammine (UN 3048)</i> Pin length : 20,5  Adaptor color : <i>grey (UN 7053)</i>			
<b>VA 50</b>	Honeywell & Braukmann Broen (Typ: Ballorex Dynamic) Johnson Controls (VG6210EC & VG6510EC, VG6210JC) Böhnisch/SBK (before 1998) Cazzaniga, Reich, MNG (before 1998) Frese EVA Basic (to 2016), Schütz Landis & Gyr, Seppelfricke, Cufix KaMo (from Sept. 2005), Bell & Gossett (Zonevalve) FAR (from 2007), Pantherm, Unicolor Sauter (VXL F220) (BUT015 F410) Siemens VDN, Spartan valve V240 emcal (stainless steel from march 2013) Sauter (BUT010 F400) (BUT015 F210) Comap HKV Modul black (H) Pantherm plastics	 <b>VA 50</b> Part-No.: 108477 Thread : M30x1,5  Adaptor color : <i>dark grey (UN 7028)</i>	 <b>VA 50 H</b> Part-No.: 108639 Thread : M30x1,5 Pin Color : <i>dark grey (UN 7028)</i> Pin length : 10  Adaptor color : <i>grey (UN 7053)</i>	 <b>VA 50 HK</b> Part-No.: 110749 Thread : M30x1,5 Pin Color : <i>dark grey (UN 7028)</i> Pin length : 15  Adaptor color : <i>light blue (UN 55088)</i>	 <b>VA 50 H-SK</b> Part-No.: 113073 Thread : M30x1,5 Pin Color : <i>dark grey (UN 7028)</i> Pin length : 10  Adaptor color : <i>grey (UN 7053)</i>	10,00











## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 53	Johnson Controls type VG5200CC, VG4400GC		 <p><b>VA 53 H</b> Part-No.: 120384 Thread : M28x1,5 Pin Color : <i>light grey (UN 7019)</i> Pin length : 9 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 53 H-SK</b> Part-No.: on request Thread : M28x1,5 Pin Color : <i>light grey (UN 7019)</i> Pin length : 9 Adaptor color : <i>grey (UN 7053)</i></p>	11,00
VA 54	MMA, Vama Tour & Andersson valve RVT-K (about '92)	 <p><b>VA 54</b> Part-No.: 108469 Thread : M28x1,5  Adaptor color : <i>dark blue (UN 5023)</i></p>	 <p><b>VA 54 H</b> Part-No.: 108637 Thread : M28x1,5 Pin Color : <i>dark blue (UN 5023)</i> Pin length : 11 Adaptor color : <i>grey (UN 7053)</i></p>	 <p><b>VA 54 HK</b> Part-No.: 110947 Thread : M28x1,5 Pin Color : <i>dark blue (UN 5023)</i> Pin length : 16 Adaptor color : <i>dark blue (UN 5023)</i></p>	 <p><b>VA 54 H-SK</b> Part-No.: 118008 Thread : M28x1,5 Pin Color : <i>dark blue (UN 5023)</i> Pin length : 11 Adaptor color : <i>grey (UN 7053)</i></p>	9,00
VA 55	MMA (Typ: FVXR 15) Johnson Controls (Type: VG5410EC, VG5800CC, VG5400CC)		 <p><b>VA 55 H</b> Part-No.: 111136 Thread : M28x1,5 Pin Color : <i>black</i> Pin length : 8,5 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 55 H-SK</b> Part-No.: 126247 Thread : M28x1,5 Pin Color : <i>black</i> Pin length : 8,5 Adaptor color : <i>grey (UN 7053)</i></p>	11,50
VA 57	Gripp Orkli		 <p><b>VA 57 H</b> Part-No.: 113474 Thread : M28x1,0 Pin Color : <i>black</i> Pin length : 8,5 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+2,7mm)</p>		 <p><b>VA 57 H-SK</b> Part-No.: on request Thread : M28x1,0 Pin Color : <i>black</i> Pin length : 8,5 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+2,7mm)</p>	14,20








## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 59	Danfoss RAV/L	 <p><b>VA 59</b> Part-No.: 109566</p> <p>Adaptor color : <i>light grey (UN 7019)</i> Flange diameter: approx 25,5mm</p>	 <p><b>VA 59 H</b> Part-No.: 111734 Thread : M30x1,5 Pin Color : <i>light grey (UN 7019)</i> Pin length : 9 Adaptor color : <i>grey (UN 7053)</i> Flange diameter: approx 25,5mm</p>		 <p><b>VA 59 H-SK</b> Part-No.: 117694 Thread : M30x1,5 Pin Color : <i>light grey (UN 7019)</i> Pin length : 9 Adaptor color : <i>grey (UN 7053)</i> Flange diameter: approx 25,5mm</p>	
VA 60	Meges Magra (old)		 <p><b>VA 60 H</b> Part-No.: 118402 Thread : M38x1,5 Pin Color : <i>cammine</i> Pin length : 22 Adaptor color : <i>grey (UN 7053)</i></p>			
VA 61	Ondal Oreg	 <p><b>VA 61</b> Part-No.: 111758 Thread : M38x1,5 Adaptor color : <i>grey (UN 7053)</i></p>	 <p><b>VA 61 H</b> Part-No.: 111412 Thread : M38x1,5 Pin Color : <i>brown</i> Pin length : 15,5 Adaptor color : <i>grey (UN 7053)</i></p>			
VA 62	Universa (from 1999) Comap manifold-Module (fawn)		 <p><b>VA 62 H</b> Part-No.: 111100 Thread : M30x1,5 Pin Color : <i>orange (UN 2002)</i> Pin length : 11,5 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 62 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : <i>orange (UN 2002)</i> Pin length : 11,5 Adaptor color : <i>grey (UN 7053)</i></p>	8,50








## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 63	Emmeti (old) Danfoss AH-QM <b>FlowCon</b> <b>Gampper Vario C, UniQ (6,5mm actuator)</b> <b>Polytherm 3-Way valve (mot. actuator 150N)</b>	 <p><b>VA 63</b> Part-No.: 124990 Thread : M30x1,5  Adaptor color : black (UN 0051)</p>	 <p><b>VA 63 H</b> Part-No.: 108915 Thread : M30x1,5 Pin Color : red (UN 3004) Pin length : 11,75 Adaptor color : grey (UN 7053)</p>	 <p><b>VA 63 HK</b> Part-No.: 110943 Thread : M30x1,5 Pin Color : red (UN 3004) Pin length : 16,75 Adaptor color : light blue (UN 55088)</p>	 <p><b>VA 63 H-SK</b> Part-No.: on request Thread : M30x1,5 Pin Color : red (UN 3004) Pin length : 11,75 Adaptor color : grey (UN 7053)</p>	8,25
VA 64	Pettinaroli	 <p><b>VA 64</b> Part-No.: 109629 Thread : M28x1,5 drilled, without Pin guidance  Adaptor color : grey (UN 7053)</p>				17,80
VA 66	Industrietechnik Italy (types: VFX4..., VFX2..., VFT3..)	 <p><b>VA 66</b> Part-No.: 122028 Thread : M30x1,5 drilled, without Pin guidance  Adaptor color : grey (UN 7053)</p>				12,50
VA 67	Industrietechnik Italy (types: VFT4..., VFX3..., VFT2..) <b>Controlli Zonenvlves (VSX, VMX, VTX)</b> <b>with 5mm actuator</b>	 <p><b>VA 67</b> Part-No.: 125823 Thread : M30x1,5 drilled, without Pin guidance  Adaptor color : grey (UN 7053)</p>				13,00





## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
VA 70	Comap (M28x1,5) Universa (before 1999) Kromschroder (Cuerpo Valve Thermostatica)		 <p><b>VA 70 H</b> Part-No.: 108643 Thread : M28x1,5 Pin Color : <i>yellow (UN 1069)</i> Pin length : 13 Adaptor color : <i>grey (UN 7053)</i></p>		 <p><b>VA 70 H-SK</b> Part-No.: 131223 Thread : M28x1,5 Pin Color : <i>yellow (UN 1069)</i> Pin length : 13 Adaptor color : <i>grey (UN 7053)</i></p>	7,00
VA 72	Danfoss RAV Danfoss FJVR		 <p><b>VA 72 H</b> Part-No.: 108907 Thread : M30x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>light grey (UN 7019)</i> Flange diameter: approx 34mm</p>			
VA 76	Danfoss RTD (complete valves)	 <p><b>VA 76</b> Part-No.: 123461 Thread : M30x1,5 Base body 'extra-high' turned out Adaptor color : <i>pure white (RAL 9010)</i></p>				20,00
VA 78	Danfoss RA Oventrop flange (Typ: V3D, GD & GDF) Jaga flange-valves Brötje radiator-valves with flange		 <p><b>VA 78</b> Part-No.: 108635  Flange diameter approx 23mm Adaptor color : <i>pure white (RAL 9010)</i></p>		 <p><b>VA 78-SK</b> Part-No.: 113141  Adaptor color : <i>pure white (RAL 9010)</i></p>	28,80
VA 79	Danfoss RTD (valve-barrel)		 <p><b>VA 79</b> Part-No.: 116919 Thread : M30x1,5 drilled, without pin guidance Adaptor color : <i>signal white (RAL 9003)</i></p>			24,50



## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
<p><b>VA 80</b></p>	<p>Heimeier, Herb, Onda, IVAR, Thermoval MNG (from 1998), Schlösser (from 1993) Mair (from 1998), Kermi, Cazzaniga corner valve Oventrop (Typ: Cocon Q, V3K) Multiblock (from 1997), Frank (from 2003) Athe-Therm (brass to Feb. 2005) Athe-Therm (stainless steel), BHS manifold Tour &amp; Andersson (from 1999), Jupiter Böhmisch/SBK (from 1998), Simplex, RBM Emmeti, Remo, Cosmo, Watts, Roth Delphis-Therm, GC-manifold, Cuprotherm Caleffi manifold Serie 670 (plastic) Wieland, Caleffi valve, Siemens VD 115CLC SKV manifold, Inteca Sauter (VXL F200 &amp; F210)(BXL F200 &amp; F210) (BUL) Sauter (BUT010 F410), VTE cornervalve (H) Aquatechnik Italy (Multirapid, before 2007, from 2009) EQ-Therm brass manifold, TKM, Brugman Johnson-Controls (Typ: V5210KC, V5510KC, V5810DC) Bianchi 662 (2-way), 663 &amp; 664 (3-way) Bianchi 4-way-valve, Jaga, Gomacal Nereus corner valve DN 10, Strasshofer Honeywell (H) (Typ: V9050, VSOF 215) Honeywell (V5823, V5833), radiodaemm Taco (Vogel &amp; Noot, Cosmo stainless.) Caleffi (with manufacturer Threading) Watts (Voogel &amp; Noot, Finimetall, Myson) Voogel &amp; Noot (Cosmo brass manifold) RDZ (brass manifold), VIR (Serie 9520, 9700) Siemens VVI46, VXI46, VVP47, VXP47, VMP47 Honeywell V2020 (MNG) IVR stainless steel HKV, Kemper stainless steel Cosmo (Objekt-Line) (CMV Modul manifold) <i>Honeywell V58x2A1063, VSMF-215 VSMF-220, VSMF415, VSMF 315, V5823A</i> Herz 3-way-valves (1 7762 xx) Herz 3-way-valves with bypass (1 7763 xx) Herz controlvalve (1 7760 xx) Herz Thermostatic valves Serie 'TS 98 VH' Unicor brass manifold, Roversy Belparts NV2D15, Wittigsthal (FT2) Tobler Stramax (220TT2-06-06S) Carlo Poletti (V1521), Therminon HKV-Modul Presblock (RTEV-M), <b>Onda-Therm HKV-Module</b> Tobler Stramax (220TTT-06-04S) AO-Therm brass manifold, Pexep Siemens VPI46 &amp; VPP46, 2.5mm Empur brass and stainless steel manifold</p>	<div style="text-align: center;">  </div> <p style="text-align: center;"><b>VA 80</b> Part-No.: 108472</p> <p>Thread : M30x1,5</p> <p>Adaptor color : <i>white grey (UN 7002)</i></p>	<div style="text-align: center;">  </div> <p style="text-align: center;"><b>VA 80 H</b> Part-No.: 108640</p> <p>Thread : M30x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>grey (UN 7053)</i></p>	<div style="text-align: center;">  </div> <p style="text-align: center;"><b>VA 80 HK</b> Part-No.: 110743</p> <p>Thread : M30x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 14,5 Adaptor color : <i>light blue (UN 55088)</i></p>	<div style="text-align: center;">  </div> <p style="text-align: center;"><b>VA 80 H-SK</b> Part-No.: 112986</p> <p>Thread : M30x1,5 Pin Color : <i>white grey (UN 7002)</i> Pin length : 9,5 Adaptor color : <i>grey (UN 7053)</i></p>	<p>10,50</p>







## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
<b>VA 81</b>	Kermi, Arbonia, Dia-Therm, Viessmann (radiator & compact-radiator with integrated valves) Te.Sa (Stramax), Tobler (Te.Sa) Strawa stainless steel manifold (before 2003)		 <p style="text-align: center;"><b>VA 81 H</b> Part-No.: 109651 Thread : M30x1,5 Pin Color : <i>light green (UN 6026)</i> Pin length : 12,25 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+3mm)</p>		 <p style="text-align: center;"><b>VA 81 H-SK</b> Part-No.: 115711 Thread : M30x1,5 Pin Color : <i>light green (UN 6026)</i> Pin length : 12,25 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+3mm)</p>	10,75





## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure A
<b>VA 90</b>	Chemidro, TECE (plastic), KWH Pipe, Prandelli (brass manifold) Athe-Therm (brass from feb. 2005) Rothh DE (H) (Typ: Universal HK2) Uponor stainless steel-manifold (to 2014) SAS brass-manifold, Somatherm INOX Luxor, Oventrop Hycocoon TM (DN32) Sauter (VUT010 F200 & F210 & F220) Tiemme brass manifold (series: 'Floor') Honeywell VSMF, Maincor stainless steel manifold Afriso pro Calida EF1 (plastic), Reliance stainless EQ-Therm stainless steel manifold	  <b>VA 90</b> Part-No.: 108919 Thread : M30x1,5  Adaptor color : <i>carmine (UN 3048)</i>	  <b>VA 90H</b> Part-No.: 118915 Thread : M30x1,5 Pin Color : <i>orange (UN 2002)</i> Pin length : 11,5 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+3mm)		  <b>VA 90H-SK</b> Part-No.: 123376 Thread : M30x1,5 Pin Color : <i>orange (UN 2002)</i> Pin length : 11,5 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+3mm)	11,50
<b>VA 94</b>	redex Lavagrund Polytech Aqua Seal		  <b>VA 94</b> Part-No.: 108628 Thread : M30x1,0 Pin Color : <i>hellyellow (UN 1033)</i> Pin length : 19 Adaptor color : <i>grey (UN 7053)</i>			-5,50
<b>VA 95</b>	Multitherm (typ: AquaHeat 76042 Prolock Deluxe)		  <b>VA 95 H</b> Part-No.: 118534 Thread : M30x1,5 Pin Color : <i>dark grey (UN 7028)</i> Pin length : 10 Adaptor color : <i>pure white (RAL 9010)</i> Adaptor is extra high (+3mm)			13,00
<b>VA 97</b>	Temset / KWC		  <b>VA 97</b> Part-No.: 109582 Pin Color : <i>light blue (UN 5025)</i> Pin length : 14 Adaptor color : <i>grey (UN 7053)</i>			7,20

## Übersicht - Ventiladapter

Stand vom 29.09.2021

Adaptor	Valve product	Flat version	High version	High version heating/cooling	High version for Protection-Cap (see info page 15)	Closing measure
<b>Special adaption</b>	Adaptors from combinations of our valve adaptors with special adaptations made by Siemens	Staefa / Siemens types: 2W..., 3W..., 4W... (flange)  <b>Combination:</b>  <b>VA 90</b> Part-No.: 108919 and Adaptor <b>AL 100</b> from Siemens (Part-No.: 113515):  	Vaillant (flange connection)  <b>Combination:</b>  <b>VA 80</b> Part-No.: 108472 and Adaptor <b>AV 59</b> from Siemens (Part-No.: 113516):  			A
<b>Information to Protection Cap</b>  <b>AA SK 1004 N</b>	The Protection-Cap protects the actuator from vandalism and mechanical damage. To mount the cap a special adaptation is needed, which has a slot to adjust the cap-bracket.  <u>Mounting advice (abstracted from manual):</u>  - put the adaptor through the bracket - mount this combination to the valve - draw the actuator and direct the cable through the bracket - engage the protection-housing on front-side of the bracket and mount it to the back-side - fasten the housing with enclosed screw  Part-No.: 118545					