

EM-KT4CEU-G

Electric scooter

Electric scooter with built-in display and application control.



HIGHLIGHTS

- 350W Motor
- Certified battery 36V 10 Ah
- Range per charge: 35 km
- Maximum speed 20 km/h
- 10" Pneumatic tyre
- Triple brake system
- Rear Suspension
- Turning indicator
- Super power mode
- e-ABS
- Rear fender with licence plate holder

Sleek Design & Advanced Control: Enjoy a refined look and precise driving parameter control. Enhanced Safety: Integrated turn signals and a front drum brake boost safety. Elegant Finish: Now available in a sophisticated gray for modern style.

e-scooter Features

Turn Indicator	Yes
APP Control	Yes
Display	LED
Bell	Yes
Tyre Pressure (PSI)	36
Tyres	Pneumatic
USB Port	Yes
Wheel Size (inches)	10
Braking	Disc brake / Drum brake / Power off brake
Charger Input (VAC/A)	100-240/1.8
Charger Output (VDC/A)	42/1.5
Driving Mechanism	Rear Wheel Brushless Motor (350W)
Foldable	Yes
IP Rating	IPX4
Maximum Incline (degrees)	15
Maximum Load (kg)	120
Maximum Speed (km/h)	20
Motor Power (Watts)	350
Range per Full Charge (km)	35
Start Mode	Kick Start
Suspension	Rear
Brake - Electronic	Yes
Brake - Front Wheel	Drum
Brake - Rear Wheel	Disc
Display Type	Alien
Turn Indicator - Handle Bar	Yes
Turn Indicators	Yes
Type of Headlight	Alien Head

Power Information

Power Requirements	100-240VAC 50/60HZ 1.8A
Power Consumption (W)	6.4
Standby Power Consumption (W)	0
Off Mode Power Consumption (W)	0
Plug	CE/UK Plug +adaptor
Auto Power Off	Yes
External AC Adapter	Yes
Safety Logo Certification	PLEV, RED, LVD, EMC, REACh, RoHS

Logistic Information

Unit Weight (kg)	20.6
Box Size (W x H x D in mm)	205 x 535 x 1215
Gross Weight (kg)	22.7
Units on EU Pallet 1.8m	12
Units on UK CHEP Pallet 1.8m	12
Dimensions Unfolded (W x H x L in mm)	615 x 1220 x 1180
Dimensions Folded (W x H x L in mm)	615 x 500 x 1180
Container Load 40HQ	484
Container Load 40	445
Container Load 20	208
Foot Plate Size (W x L in mm)	160 x 483
Foot Plate to Top of Handlebars (mm)	1025
Ground to Foot Plate (mm)	180
Box Staking Quantity	3
EAN	5905683272070