
TOGETHER, WE GET IT DONE.™

TECHNICAL DATA

v04
Creation date
14/07/2026



Net fill	Packaging
250ml	Aerosol

CRC Dry Lube

Dry, non greasy surface lubrication.

KEY FEATURES

- Does not contain PTFE.
- Clean, dry and non-oily.
- Functional over a wide temperature range.
- Produces a very low coefficient of friction.
- Most effective when low speeds and light loads are involved.
- High temperature resistance.
- Safe on most rubbers, plastics and coatings.

APPLICATION AREA

- Coin mechanisms
- Plastic drives and sliding mechanisms.
- Fine mechanics.
- Pneumatic tools.
- Precision instruments.
- Valves.
- Surface treatment.
- Release agent for moulding plastic and rubber.

DIRECTIONS FOR USE

- Shake well before use.
- Shake until the agitator ball moves freely in the can.
- To remove residues or excess product, use one of the CRC cleaners.
- Spray from a distance of approximately 20 - 30 cm.
- Allow to dry at room temperature.
- Do not use on energized equipment.
- Test on sensitive or stressed material.
- Transfer of CRC Dry Lube to moulded parts is negligible, minimizing interference with post finishing operations.

CRC INDUSTRIES EUROPE

Touwslagerstraat 1 – 9240 Zele –
Belgium P: +32 (0)52 45 60 11

(Operating) temperature range - en-BE	-150°C to +900°C
Density 20°C	0.86-0.91
Drying time	15 min
Flash point	*-40*
Odour	Alcohol
Colour	White
Coefficient of Static Friction (µs)	0,38
Thermal conductivity	High (dissipates heat)

HEALTH AND SAFETY

A Safety Data Sheet (SDS) according to EC Regulation N° 1907/2006 Art.31 and amendments are available for all CRC products

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

Disclaimer All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment and conditions and the unpredictable human factors involved, we recommend that our products be tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised at this moment for reason such as legislation, availability of components and newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: www.crcind.com.

CRC INDUSTRIES EUROPE

Touwslagerstraat 1 – 9240 Zele –
Belgium P: +32 (0)52 45 60 11