



MAKE IT LAST.

KYOCERA SENCO Netherlands B.V.
Pascallaan 88
8218 NJ Lelystad, The Netherlands
Tel: +31 (0)320 29 55 75
info@kyocera-senco.eu
www.kyocera-senco.eu

DECLARATION OF PERFORMANCE
1L27ASBC



SENCO 2,8 x 75 mm Ring shank Coil Nail, HDG 55 µm

Intended use/ uses and identification of the construction product	
Manufacture	Kyocera Senco Netherlands, Pascallaan 88, 8218 NJ Lelystad
Intended use	For structural timber products
Unique identification	1L27ASBC
DOP number	1L27ASBC
Coating type	3
On the basis of technical specification	EN 14592:2008+A1:2012
AVCP System	3
Notified body	1015

Declared performances				
Essential Characteristics for:			1L27ASBC	
			Performance	
$M_{y,k}$	Characteristic Yield Moment	[Nmm]	3181	
$f_{ax90,k}$	Characteristic Withdrawal parameter (350 kg/m ³)	[N/mm ²]	7,75	
$f_{ax0,k}$	Characteristic Withdrawal parameter (350 kg/m ³)	[N/mm ²]	4,10	
$f_{head,k}$	Characteristic head pull-through parameter (350 kg/m ³)	[N/mm ²]	22,08	
$f_{tens,k}$	Tensile Capacity	[kN]	4,22	
Durability against corrosion			Hop Dipped Galvanized 55 µm, Service Class 1, 2 & 3 acc. Eurocode 1992-1-1	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of Kyocera Senco Netherlands B.V by:

Place and date of issue: Lelystad, 01-05-2023

Lars Aa. Mortensen

Technical Manager, KYOCERA SENCO EMEA